

Modular Acoustic Enclosures


24 – 220 kVA Range



www.FGWilson.com

The intelligent and striking design of the 24 – 220 kVA enclosure range meets the demands of diverse applications. Extremely durable, the enclosures are designed to resist corrosion and handling damage.

Developed through continuing research and development by our specialist engineers, all FG Wilson enclosures are weather resistant and incorporate internally mounted exhaust silencers. These enclosures reduce sound levels to comply with the stage 2 levels of the European Community Directive 2000/14/EC which became effective 3 January 2006.



Excellent Access for Maintenance

- » Side hinged doors on both sides of the enclosure incorporating lift-off hinges at 45 degrees
- » Radiator fill via removable, flush mounted rain cap fitted with compression seal
- » Lube oil drain valves / Coolant drain valves
- » Removable end panels allow access to radiator, exhaust outlet and alternator rear
- » Doors positioned for optimum access to frequently serviced items

Robust/Highly Corrosion Resistant Construction

- » Manufactured from galvanised steel
- » Advanced powder coating paint finish
- » Single piece main roof
- » Baseframe extends beyond enclosure protecting against handling damage
- » Minimal external fixings exposed to environment
- » Zinc plated fasteners
- » Corner posts and air handling units manufactured from high grade composite material



Transportability

- » Optional tested and certified lifting arch
- » Lifting and drag points on baseframe facilitating handling from both sides

Security and Safety

- » Secure, lockable doors prevent unauthorised access to control panel, fuel fill and battery
- » Emergency stop button mounted on exterior, convenient to control panel
- » Cooling fan and battery charging alternator fully guarded

Sound Pressure Levels (dBA) for CAE Enclosure


Generator Set Model			50 Hz						60 Hz					
			15 m (50 ft)		7 m (23 ft)		1 m (3 ft)		15 m (50 ft)		7 m (23 ft)		1 m (3 ft)	
			75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load
P33-3	Prime	93	60.5	61.8	66.5	67.8	76.3	78.4	60.6	62.7	66.6	68.7	77.6	79.9
	Standby	93	60.9	62.4	66.9	68.4	76.9	79.4	61.2	63.8	67.2	69.8	78.2	81.1
P33-6	Prime	94	59.4	61.3	65.4	67.3	76.5	78.6	–	–	–	–	–	–
	Standby	94	60.0	62.1	66.0	68.1	77.1	79.6	–	–	–	–	–	–
P50-3	Prime	93	56.7	57.7	62.7	63.7	76.7	77.9	59.7	60.8	65.7	66.8	79.5	80.8
	Standby	93	56.9	58.2	62.9	64.2	77.0	78.5	60.1	61.5	66.1	67.5	80.0	81.6
P50-4	Prime	90	55.7	56.4	61.7	62.4	75.3	75.5	–	–	–	–	–	–
	Standby	90	55.9	56.7	61.9	62.7	75.4	75.6	–	–	–	–	–	–
P55-3	Prime	93	56.9	58.2	62.9	64.2	77.0	78.5	60.1	61.5	66.1	67.5	80.0	81.6
	Standby	93	57.3	58.9	63.3	64.9	77.4	79.2	60.5	62.2	66.5	68.2	80.5	82.4
P55-4	Prime	91	56.2	56.5	62.2	62.5	75.3	75.5	–	–	–	–	–	–
	Standby	91	56.3	56.7	62.3	62.7	75.3	75.6	–	–	–	–	–	–
P65-5	Prime	93	57.6	59.4	63.6	65.4	77.8	79.7	61.0	63.0	67.0	69.0	81.0	83.3
	Standby	93	58.1	60.5	64.1	66.5	78.3	80.8	61.5	63.8	67.5	69.8	81.6	84.2
P65-6	Prime	91	57.7	58.5	63.7	64.5	75.8	77.1	–	–	–	–	–	–
	Standby	91	57.9	58.9	63.9	64.9	76.2	77.8	–	–	–	–	–	–
P88-3	Prime	92	57.7	59.1	63.7	65.1	76.0	77.0	60.6	61.2	66.6	67.2	79.0	79.5
	Standby	92	58.1	59.8	64.1	65.8	76.2	77.4	60.8	61.5	66.8	67.5	79.2	79.6
P88-6	Prime	96	61.3	61.4	67.3	67.4	80.1	80.2	–	–	–	–	–	–
	Standby	96	61.3	61.5	67.3	67.5	80.2	80.3	–	–	–	–	–	–
P110-3	Prime	96	62.4	63.1	68.4	69.1	80.4	81.0	65.2	65.4	71.2	71.4	84.4	84.6
	Standby	96	62.6	63.5	68.6	69.5	80.6	81.3	65.2	65.5	71.2	71.5	84.5	84.7
P110-6	Prime	94	61.4	61.6	67.4	67.6	80.2	80.3	–	–	–	–	–	–
	Standby	94	61.5	61.7	67.5	67.7	80.2	80.4	–	–	–	–	–	–
P150-5	Prime		60.0	60.5	66.0	66.5	78.8	79.1	60.7	61.1	66.7	67.1	81.0	81.1
	Standby		60.1	60.7	66.1	66.7	78.8	79.2	60.8	61.3	66.8	67.3	81.0	81.2
P165-5	Prime		58.5	58.9	64.5	64.9	78.0	78.2	61.3	61.9	67.3	67.9	82.1	82.4
	Standby		58.6	59.1	64.6	65.1	78.1	78.3	61.5	62.1	67.5	68.1	82.2	82.7
P200-3	Prime	97	62.3	63.5	68.3	69.5	80.0	80.7	64.9	65.2	70.9	71.2	84.2	84.3
	Standby	97	62.7	64.0	68.7	70.0	80.2	81.1	65	65.3	71	71.3	84.3	84.4
P220-3	Prime	97	62.3	63.5	68.3	69.5	80.0	80.7	–	–	–	–	–	–
	Standby	97	62.7	64.0	68.7	70.0	80.2	81.1	–	–	–	–	–	–

Levels in accordance with European Noise Directive (2000/14/EC).

Sound Pressure Levels (dBA) for CAE Enclosure

Generator Set Model			50 Hz						60 Hz					
			15 m (50 ft)		7 m (23 ft)		1 m (3 ft)		15 m (50 ft)		7 m (23 ft)		1 m (3 ft)	
			75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load
P26-3S	Prime	93	60.5	61.8	66.5	67.8	76.3	78.4	60.6	62.7	66.6	68.7	77.6	79.9
	Standby	93	60.9	62.4	66.9	68.4	76.9	79.4	61.2	63.8	67.2	69.8	78.2	81.1
P26-6S	Prime	94	60.5	61.8	66.5	67.8	76.3	78.4	–	–	–	–	–	–
	Standby	94	60.9	62.4	66.9	68.4	76.9	79.4	–	–	–	–	–	–
P40-3S	Prime	93	56.7	57.7	62.7	63.7	76.7	77.9	59.7	60.8	65.7	66.8	79.5	80.8
	Standby	93	56.9	58.2	62.9	64.2	77.0	78.5	60.1	61.5	66.1	67.5	80.0	81.6
P40-4S	Prime	90	55.7	56.4	61.7	62.4	75.3	75.5	–	–	–	–	–	–
	Standby	90	55.9	56.7	61.9	62.7	75.4	75.6	–	–	–	–	–	–
P50-5S	Prime	–	58.1	59.1	64.1	65.1	76.6	77.3	61.1	62.1	67.1	68.1	78.9	80.0
	Standby	–	58.5	59.5	64.5	65.5	76.9	77.6	61.4	62.5	67.4	68.5	79.3	80.5
P55-6S	Prime	–	57.7	58.5	63.7	64.5	75.8	77.1	–	–	–	–	–	–
	Standby	–	57.9	58.9	63.9	64.9	76.2	77.8	–	–	–	–	–	–
P90-3S	Prime	–	62.2	62.8	68.2	68.8	80.2	80.8	65.1	65.3	71.1	71.3	84.4	84.6
	Standby	–	62.4	63.1	68.4	69.1	80.4	81.0	65.2	65.4	71.2	71.4	84.4	84.6
P90-6S	Prime	–	61.3	61.5	67.3	67.5	80.2	80.3	–	–	–	–	–	–
	Standby	–	61.4	61.6	67.4	67.6	80.2	80.3	–	–	–	–	–	–

Levels in accordance with European Noise Directive (2000/14/EC).



Dimensions and Weights for CAL/CALG Enclosure

Generator Set Model	A: mm	B: mm	C: mm	D*: mm	Weight: kg	Fuel Capacity: l
Three Phase Models						
P33-3	2120 (83.5)	970 (38.2)	1525 (60.0)	718 (28.3)	1002 (2209)	161 (43.0)
P33-6	2120 (83.5)	970 (38.2)	1525 (60.0)	718 (28.3)	1002 (2209)	161 (43.0)
P50-3	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1237 (2727)	219 (58.0)
P50-4	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1229 (2709)	219 (58.0)
P55-3	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1237 (2727)	219 (58.0)
P55-4	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1277 (2815)	219 (58.0)
P65-5	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1279 (2820)	219 (58.0)
P65-6	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1319 (2908)	219 (58.0)
P88-3	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1416 (3122)	219 (58.0)
P88-6	2770 (109.1)	1120 (44.1)	1525 (60.0)	896 (35.3)	1554 (3426)	250 (66.0)
P110-3	2770 (109.1)	1120 (44.1)	1525 (60.0)	896 (35.3)	1615 (3560)	250 (66.0)
P110-6	2770 (109.1)	1120 (44.1)	1525 (60.0)	896 (35.3)	1744 (3845)	250 (66.0)
P150-5	3520 (138.6)	1010 (39.8)	1815 (71.5)	1145 (45.1)	1975 (4354)	349 (92.2)
P165-5	3520 (138.6)	1120 (44.1)	1815 (71.5)	1145 (45.1)	2113 (4658)	349 (92.2)
P200-3	3520 (138.6)	1320 (52.0)	1815 (71.5)	1080 (42.5)	2273 (5011)	418 (110.4)
P220-3	3520 (138.6)	1320 (52.0)	1815 (71.5)	1080 (42.5)	2203 (4857)	418 (110.4)
Single Phase Models						
P26-3S	2120 (83.5)	970 (38.2)	1525 (60.0)	718 (28.3)	991 (2185)	161 (43.0)
P26-6S	2120 (83.5)	970 (38.2)	1525 (60.0)	718 (28.3)	991 (2185)	161 (43.0)
P40-3S	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1247 (2749)	219 (58.0)
P40-4S	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1199 (2643)	219 (58.0)
P50-5S	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1340 (2954)	219 (57.0)
P55-6S	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1355 (2987)	219 (58.0)
P90-3S	2770 (109.1)	1120 (44.1)	1525 (60.0)	899 (35.4)	1613 (3556)	250 (66.0)
P90-6S	2770 (109.1)	1120 (44.1)	1525 (60.0)	899 (35.4)	1653 (3644)	250 (66.0)

*Clearance required both sides; Weight with lube oil, no coolant, no fuel.

FG Wilson manufactures product in the following locations:

Northern Ireland • Brazil • China • India • USA

With headquarters in Northern Ireland, FG Wilson operates through a Global Dealer Network.
To contact your local Sales Office please visit the FG Wilson website at www.FGWilson.com.

FG Wilson is a trading name of Caterpillar (NI) Limited.

In line with our policy of continuous product development, we reserve the right to change specification without notice.

24-220 kVAEnclosure/0216/GB